

S452M-C4



Products Low Voltage Products and Systems Modular DIN Rail Products Miniature Circuit Breakers MCBs

General Information

Extended Product Type:	S452M-C4
Product ID:	2CCS472001R0044
EAN:	7612270106288
Catalog Description:	Miniature Circuit Breakers MCBs - MCB SMISLINE Classic S452 - 2P - C
Long Description:	S452M-C4 Miniature Circuit Breaker 2 Poles C Characteristic 4A 10000 ~230/400V

Additional Information

ABB Industrial IT Suite:	Control IT
Country of Origin:	Switzerland (CH)
Customs Tariff Number:	85362020
Data Sheet, Technical Information:	2CCC451027C0105
Declaration of Conformity - CE:	2CCC451034D0201
Dimension Diagram:	2CCC451032C0101
EAN:	7612270106288
ETIM 4:	EC000042 - Miniature circuit breaker (MCB)
ETIM 5:	EC000042 - Miniature circuit breaker (MCB)
ETIM 6:	EC000042 - Miniature circuit breaker (MCB)
Environmental Information:	2CCC404013D0201
Frequency (f):	50 ... 60 Hz
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	2CCC404015M0104
Invoice Description:	S452M-C4
Minimum Order Quantity:	1 piece
Number of Poles:	2
Object Classification Code:	FC
Package Level 1 EAN:	7612270106288
Package Level 1 Gross Weight:	1540 g
Package Level 1 Height:	89 mm
Package Level 1 Length:	101 mm
Package Level 1 Units:	5 piece
Package Level 1 Width:	185 mm
Power Loss:	3.8 W
Product Depth:	94.5 mm
Product Main Type:	MCB SMISLINE Classic S452
Product Name:	Miniature Circuit Breakers MCBs
Product Net Depth:	94.5 mm
Product Net Height:	89 mm
Product Net Length:	94.5 mm
Product Net Weight:	0.284 kg
Product Net Width:	69 mm
Rated Current (I_n):	4 A
Rated Operational Current (I_b):	4 A
Rated Operational Voltage:	230 / 400 V AC
Rated Short-Circuit Capacity (I_{cn}):	10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	25 kA
RoHS Information:	2CCC451034D0201
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	S452M-C4 Miniature Circuit Breaker 2 Poles C Characteristic 4A 10000 ~230/400V
Size:	2 modules
Standards:	IEC/EN 60898-1 , IEC/EN 60947-2
Tripping Characteristic:	C

