

Appearance	Sensing distance	Optical modulation	Features	Output configuration	Indicator*	Model		Page
						NPN output	PNP output	
	5 mm (slot width)	Non-modulated light	General-purpose models with connectors Emitter/receiver window 	Dark-ON	---	EE-SX670	EE-SX670P	55
				Light-ON (selectable)		EE-SX670A	EE-SX670R	
Light-ON				---	EE-SX470	EE-SX470P		
				Dark-ON	---	EE-SX671	EE-SX671P	
				Light-ON (selectable)		EE-SX671A	EE-SX671R	
Light-ON				---	EE-SX471	EE-SX471P		
				Dark-ON	---	EE-SX672	EE-SX672P	
				Light-ON (selectable)		EE-SX672A	EE-SX672R	
Light-ON				---	EE-SX472	EE-SX472P		
				Dark-ON	---	EE-SX673	EE-SX673P	
				Light-ON (selectable)		EE-SX673A	EE-SX673R	
Light-ON				---	EE-SX473	EE-SX473P		
				Dark-ON	---	EE-SX674	EE-SX674P	
				Light-ON (selectable)		EE-SX674A	EE-SX674R	
Light-ON				---	EE-SX474	EE-SX474P		
				Dark-ON Light-ON (selectable)	---	EE-SX676	EE-SX676P	
					---	EE-SX677	EE-SX677P	

**Note:** The table includes only basic specifications. Be sure to check the detailed specifications and precautions on the page given in the right column before using the Photomicrosensor.